

**Chapter 19.29**  
**R-1-6 -- RESIDENTIAL SINGLE-  
FAMILY ZONE**

**Sections:**

- 19.29.010 Purpose.**
- 19.29.020 Permitted uses.**
- 19.29.030 Conditional uses.**
- 19.29.040 Minimum lot size.**
- 19.29.050 Minimum lot width.**
- 19.29.060 Setbacks/yard requirements.**
- 19.29.070 Maximum height of structures.**
- 19.29.080 Maximum lot coverage.**
- 19.29.090 Open space requirement.**

**19.29.010 Purpose.**

The purpose of the R-1-6 zone is to allow for the establishment of single-family homes organized in medium-density neighborhoods characteristic of traditional suburban residential developments.

**19.29.020 Permitted uses.**

Permitted uses in the R-1-6 zone are as follows:

- A. Single-family detached dwellings; and
- B. Accessory buildings customary to single-family housing.

**19.29.030 Conditional uses.**

Conditional uses in the R-1-6 zone are as follows:

- A. Churches and private non-profit recreational grounds associated with that use;
- B. Planned unit development;
- C. Public and quasi-public uses; and
- D. Wireless telecommunication towers.

**19.29.040 Minimum lot size.**

The minimum lot size in the R-1-6 zone is 6,000 square feet.

**19.29.050 Minimum lot width.**

The minimum lot width in the R-1-6 zone is 60 feet measured at the front setback.

**19.29.060 Setbacks/yard requirements.**

A. Setbacks/yard requirements are intended to provide a description of the required space between buildings and property lines. All buildings intended for human inhabitants shall maintain a minimum distance from property lines as follows:

1. Front: 20 feet.
2. Sides: On interior lots, a total of at least 15 feet between the two side yards, with no side yard of less than five feet. On corner lots, at least 15 feet per side yard.
3. Rear: 20 feet.

B. Accessory buildings in the R-1-6 zone shall maintain a minimum distance from property lines as follows:

1. Front: Accessory buildings, including detached garages, shall maintain a setback of at least six feet from the main building in the rear yard of the particular property.
2. Sides: Three feet on interior lots; 20 feet on the street side of corner lots.
3. Rear: Three feet on interior lots; 20 feet on the street side of corner lots.

C. Attached garages shall conform to the rear yard requirements of main buildings.

**19.29.070 Maximum height of structures.**

A. For uses where the slope of the original ground surface is greater than 15%, or if the property is located in a sensitive lands overlay zone, the maximum structure height shall be 30 feet.

B. All other properties shall maintain a maximum structure height of 35 feet.

C. No accessory structure shall exceed 20 feet in height. For each foot of height over 14 feet, accessory structures shall be set back from property lines an additional foot from the minimum setback to allow a maximum height of 20 feet.

**19.29.080 Maximum lot coverage.**

The maximum lot coverage for the R-1-6 zone is 50%, including all structures.

**19.29.090 Open space requirement.**

The minimum open space requirement for developments over five acres in the R-1-6 zone is ten percent for standard subdivisions. For PUD's, the minimum open space shall be determined by the planning commission, but shall not be less than 15%.